



# **B&T BEARING INC.**<sup>™</sup>

BALL TRANSFER UNITS & CARGO HANDLING EQUIPMENT

## **Impact and UV Resistant Conveyor PVC Rollers**

- ▶ **Ideal for package handling, conveyor and conveying**
- ▶ **Rated for a temperature range from -10°F to 140°F**
- ▶ **Performs well both outdoors and indoors**
- ▶ **Well-suited for use in high-volume and high-impact areas**
- ▶ **Roller material: Impact and UV Resistant PVC**
- ▶ **Light-weight (weighs less than aluminum rollers)**
- ▶ **Bearing type: 125 lb. rated bearings**
- ▶ **Shaft material: carbon steel, stainless steel and aluminum**
- ▶ **Shaft finish: mill finish**
- ▶ **Roller diameter: 1.90 inches**
- ▶ **1/4 inch diameter round shaft**
- ▶ **7/16 Hex shaft**
- ▶ **Custom length (up to 32 inches)**
- ▶ **Spring loaded for easy installation**

Our tough Impact and UV Resistant Conveyor PVC Rollers are suitable for a variety of conveyor and conveying applications. These rollers perform well in package handling and light-duty unloading facilities, both inside and outside.

They are particularly well-suited for use in high-volume and/or high-impact areas, because they are long-lasting and virtually unbreakable. These conveyor rollers do not crack or shatter when force is applied.

Our rollers are rated for a temperature range from -10°F to 140°F. Thus they are ideal for outside use in any climate and perform well in harsh indoor conditions. These conveyor rollers are UV resistant; therefore, they do not become brittle or break-down due to sunlight.

